

GRIP-IT T FOR TILES

Heavy Duty Anti-Slip Treatment for Ceramic, Porcelain and Tessellated Tiles



DESCRIPTION: GRIP-IT T FOR TILES is a *Professional Grade* anti-slip treatment to create a permanent slip resistant micro-texture on the glaze of the tile. It is NOT a sealer or a coating. It will not peel or wear off or go yellow. Makes wet, slippery, surfaces safer e.g. bathrooms, kitchens, lounge rooms, swimming pool areas, balconies, living areas, main entrances, corridors etc

HOW DOES IT WORK: It works by micro-etching the glaze of the tile. The longer it is allowed to dwell on the surface, the more micro-texture it creates, the more slip resistance is created. **It is a permanent treatment.**

WORKS ON: For glazed and unglazed ceramic, porcelain and tessellated tiles in domestic, commercial, indoor and outdoor areas. For homes, supermarkets, airports, hotels, building foyers, retail stores, kitchens, restaurants, bars etc

TEST FIRST: Always test first in an inconspicuous area or on a spare tile to determine ease of application, the dwell time required to achieve the slip resistance you are happy with, colour and surface look stability and overall desired results. User must determine suitability for their use.

PRECAUTIONS:

1. Read entire label, SDS and technical bulletin before using;
2. Use when surface temperature is between 4°C and 28°C;
3. **DO NOT POUR DIRECTLY FROM BOTTLE ONTO THE SURFACE;**
4. Do **NOT** allow product to come in contact with any polished or acid sensitive or non-recommended surfaces;
5. Do not pour in metal containers or mix with other chemicals;
6. May affect dark tiles, dark grouts, metal and polished surfaces;
7. Depending on how much anti-slip micro-texture is created, some dark coloured tiles can lighten in colour and polished porcelain will start to lose it's polished finish going from polished to satin to matt.

SAFETY DIRECTIONS: CORROSIVE

1. Wear protective gloves, eye, skin and foot protection when using;
2. Remove metal jewellery before using - corrosive to all metals;
3. Do **NOT** breathe fumes, vapours or spray - wear appropriate mask;
4. **TOXIC** - Do NOT eat, drink or smoke when using this product ;
5. No contact with skin. May cause burns. Do **NOT** kneel in product.
6. Obtain calcium gluconate gel to neutralise if product gets on skin.

WHAT YOU NEED BEFORE YOU START:

1. Protective gloves, eye, skin & foot protection and a watch for timing;
2. **XTREMECLEAN+** or **STONE WASH+** to clean & prepare the surface;
3. Plastic buckets plus clean sponge, roller or mop to apply the product;
4. Hose or separate bucket & mop plus plenty of clean water for rinsing;
5. **TIP:** Use a wet vac to help remove **GRIP-IT T** from the tile surface before rinsing with clean water;

SURFACE PREPARATION:

Use **XTREMECLEAN+** or **STONEWASH+** as per label instructions to ensure a clean, dry surface before starting.

HOW TO USE:

1. Sweep, vacuum or wipe tiles for a clean, dry surface;
2. Pour **GRIP-IT T FOR TILES** into a PLASTIC paint tray, bucket or container;
3. Carefully apply **GRIP-IT T FOR TILES** evenly to tile surface with a suitable clean sponge, roller or mop - **DO NOT SPRAY**;
4. Allow to dwell initially for about 5 minutes - "the dwell period";
5. After the 5 minute "dwell period", test the amount of slip resistance created by using your shoe or a gloved hand in a scuffing/rubbing motion in the standing solution and make sure you keep track of the "dwell time";
6. If you are happy with the slip resistance created, rinse thoroughly with clean water (**TIP:** Use a wet vac to remove **GRIP-IT T** before rinsing)
7. **NOTE:** If more slip resistance is required, leave the product on the surface longer and keep testing the amount of slip resistance created every 5 minutes as per STEP 5 until you achieve the desired result;
8. Repeat the process as necessary to achieve your desired slip resistance;
9. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE - ADD MORE PRODUCT TO KEEP IT WET AND ACTIVE ON THE SURFACE;**


MAINTENANCE:

After successfully treating the surface, these products will help ensure the slip resistance is properly maintained.

- **EZYCLEAN+** for routine daily/weekly cleaning;
- **XTREMECLEAN+** for periodic heavy duty cleaning;

NOTE: To reduce soiling and staining plus make the ongoing cleaning and maintenance easier, seal the treated surface with **AQUA-SEAL GOLD+**®


HOW TO USE QUICK GUIDE:



Pour product into a plastic container



Apply product evenly to a clean, dry surface



Allow to dwell for approx 5 minutes or longer as needed



After the dwell time, use a shoe to test anti-slip created



TIP: Remove Grip-It T for Tiles with a wet vac



Rinse thoroughly - tiles are now slip resistant

COVERAGE:

Approximately 10-15m² per 1 litre depending on slip resistance required and how many times the process needs to be repeated.

HANDLING, STORAGE AND CLEAN UP:

Close container tightly after each use and keep upright; Store locked up in original container in a well ventilated cool area and protect from sunlight; Shelf life is approximately 3 years in unopened container - less after opening; Storage beyond that time does not necessarily mean the product is not usable. Do not re-use container. Rinse and discard in rubbish; Wash tools, gloves and shoes with water before they dry; **WASH UNDERSIDE OF SHOES BEFORE STEPPING ONTO OTHER AREAS.**

FIRST AID:

Immediately contact Poisons Information Centre (Aust 131 126, NZ 0800 764766) or a doctor. Ingestion: Do NOT induce vomiting. Immediately rinse mouth with water and call a Poison Centre or doctor. Eyes: Immediately flush eyes with clean, running water for at least 15 minutes and see a doctor. Skin and Hair: Remove contaminated clothing. Immediately flush contaminated skin and hair under running water for 15 minutes then apply calcium gluconate gel. Inhalation: Remove victim from exposure, to fresh air. Seek medical advice. General: If irritation persists or feeling unwell, seek medical attention.

DANGER

UN3264, CORROSIVE LIQUID. ACIDIC, INORGANIC, N.O.S
CAUSES SEVERE SKIN BURNS & EYE DAMAGE
HARMFUL IF INHALED - TOXIC IF SWALLOWED
KEEP AWAY FROM SKIN & EYES - DO NOT KNEEL IN PRODUCT
Ammonium Bi-fluoride 30g/L



PRODUCT WARRANTY - SEALERS PLUS (AN AQUA-SEAL BRAND) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**



SEALERS PLUS (AN AQUA-SEAL BRAND)

P: +61 2 9521 4000 Mon - Fri 9.00am-4.00pm E: sales@sealersplus.com.au

AUS: www.sealersplus.com.au NZ: www.sealersplus.co.nz Global: www.sealersplus.com



© Copyright March 2024